

	Standard	Result
 Size	ISO 24342	See separate table
 Thickness	ISO 24346	2.0 mm
 Wear layer	ISO 24340	0.3 mm
Surface treatment		K-Guard+ PU coating
Warranty ¹	Commercial Domestic	10 years light commercial wear Lifetime wear
 Bevelled edge		No
 Standards	EN ISO 10582	Pass
 Classification	ISO 10874 - Commercial ISO 10874 - Domestic	31: Commercial moderate 23: Domestic heavy
 Reaction to fire	AS/NZS ISO 9239.1:2010	CRF: 8.1 kW/m ² Smoke value: 42% min.
 Staining resistance	EN ISO 26987	Excellent
 Light fastness	ISO 105-B02	Pass (≥ 6)
 Abrasion resistance	ISO 10582	Type 1
 Flexibility	ISO 24344	Pass
 Dimensional stability	ISO 23999	Pass (≤ 0.25%)
 Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 1 dB
 Electrical behaviour body voltage	EN 1815	Pass
 Indentation - residual	ISO 24343-1	Pass (≤ 0.1 mm)
 Castor chair continuous use	ISO 4918	Pass
 Thermal resistance	ISO 8302	0.0100 m ² K/W Suitable for underfloor heating. Max 27°C
 Slip resistance ²	AS/NZS 4586:2013	See separate table
 Adhesive	General use: High temperature:	Karndean Mega-Bond Two-part chemical cure adhesive or, One-part modified silane heat and moisture resistant adhesive
Environmental	Floorscore SCS-EC10.3-2014 v4.0 Indoor Air Comfort Environmental Product Declaration NSF/ANSI 332 ISO 14001 / ISO 9001	Indoor air quality certified; Compliant low emitting VOC emissions. Gold certification Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification) Sustainability Assessment for Resilient Floor Coverings; Conformant product Manufactured to quality and environment management systems standards
 Recycling		Suitable
 Phthalate free		Yes

¹ Subject to terms. Please see our website.

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

Every Karndean range and format meets our certification policy standards - be sure to verify the current certification status

For more information:

Call: 1800 33 11 70
Email: customerservice@karndean.com.au
Visit: www.karndeancommercial.com or www.karndean.com

May 25



	Product Code	Size		Box Quantity		Slip Resistance
		mm	inches	m ²	Pieces	
Wood Designs	KP94-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
	KP95-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
	KP96-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
	KP99-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
	KP104-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
	KP105-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
	KP138-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
	KP141-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
	KP143-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
	KP144-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
	KP146-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
	KP147-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
	KP149-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
	KP150-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
	KP153-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
	KP157-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10, P2
Stone Designs	ST16	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9, P3
	ST17	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9, P3
	ST19	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9, P3
	ST20	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9, P3
	ST21	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9, P3
	ST22	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9, P3