























	Standard	Result
 Size	ISO 24342	1500.0 mm x 250.0 mm
 Thickness	ISO 24346	4.5 mm
 Wear layer	ISO 24340	0.55 mm
Surface treatment		K-Guard+ PU coating
Backing		PVC Friction Pad
Warranty ¹	Commercial Residential	15 years wear Lifetime wear
 Bevelled edge		No
 Standards	ISO 10582	Pass
 Classification	ISO 10874 - Commercial ISO 10874 - Domestic	33: Commercial heavy 23: Domestic heavy
 Reaction to fire	AS/NZS ISO 9239.1:2003	CRF: 8.3 kW/m ² Smoke Value: 143% min.
 Staining resistance	EN ISO 26987	Excellent
 Light fastness	ISO 105-B02	Pass (≥ 7)
 Abrasion resistance	ISO 10582	Type 1
 Flexibility	ISO 24344	Pass
 Dimensional stability	ISO 23999	Pass (≤ 0.10%)
 Acoustic impact noise reduction	ISO 140-8 Improved Impact Sound Insulation ASTM E492-09 Impact Insulation Class	ΔL _w = 14 dB IIC 56 dB Suitable for use on upper floors of residential high-rise apartment buildings without the need for a separate acoustic underlay under certain build specifications - precise details available from Karndean. NCC 2016 F5.3 (a) result refers to Karndean INSUL Marshall Day Software report for your MULTI Res specification including AAAC Star rating
 Electrical behaviour body voltage	EN 1815 AATCC 134-1996	Pass Pass
 Indentation - residual	ISO 24343-1	Pass (≤ 0.1 mm)
 Castor chair continuous use	ISO 4918	Pass
 Thermal resistance	ISO 8302	0.0245 m ² K/W Suitable for underfloor heating. Max 27°C
 Slip resistance ²	AS/NZS 4586:2013	See separate table
 Adhesive		Karndean Hi-Tack P5 Adhesive when applicable; please refer to our installation instructions.
 Environmental	GBCA/NZGBC GreenStar Rating System Floorscore SCS-EC10.3-2014 v4.0 Indoor Air Comfort Environmental Product Declaration NSF/ANSI 332 ISO 14001 / ISO 9001	GreenRate Level 'A'; LCA Silver Plus; Best Practice PVC Indoor air quality certified; Compliant low emitting VOC emissions. Gold certification Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification) Sustainability Assessment for Resilient Floor Coverings; Silver certified product Manufactured to quality and environment management systems standards
 Recycling		Suitable
 Phthalate free		Yes

¹ Subject to terms

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors including but not limited to: product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

Every Karndean range and format meets our certification policy standards - be sure to verify the current certification status

For more information:

Call: 1800 33 11 70

Email: customerservice@karndean.com.au

Visit: www.karndeancommercial.com or www.karndean.com

May 25



Product Code	Size		Box Quantity		Slip Resistance Oil-Wet Ramp
	mm	inches	m ²	Pieces	
LLP301	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP302	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP304	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP306	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP307	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP308	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP310	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP311	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP312	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP313	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP314	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP316	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP317	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP325	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP326	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP327	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP328	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP329	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP331	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP334	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP335	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP352	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP353	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP354	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP355	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP356	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2
LLP357	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10, P2

Wood Designs