
























	Standard	Result
 Size	ISO 24342	1220.0 mm x 180.0 mm
 Thickness	ISO 24346	5.5 mm
 Wear layer	ISO 24340	0.55 mm
Locking system¹		5G® Fold Down installation system
Surface treatment		K-Guard+ PU coating
Warranty²	Commercial Domestic	15 years wear Lifetime wear
 Bevelled edge		Micro
 Standards	EN 16511	Pass: Multilayer modular floorcovering panels
 Classification	ISO 10874 - Commercial ISO 10874 - Domestic	33: Commercial heavy 23: Domestic heavy
 Reaction to fire	AS ISO 9239.1:2003	CRF: 10.4 kW/m ² Smoke value: 200% min.
 Staining	EN 438-2	Pass (grade 5)
 Light fastness	EN ISO 105-B02	Pass (≥ 6)
 Abrasion resistance	EN 13329 Annex E	Pass (> 4000 cycles)
 Furniture chair leg	EN 424	Pass (no visible damage)
 Dimensional stability	BS EN ISO 23999	Pass (≤ 0.25%)
 Swelling	ISO 24336	Pass (0.2%)
 Acoustic impact noise reduction	EN ISO 10140-1:2016 NCC F5.3(a) requirement of ≤ 62 dB under ISO 717.2:2013 G6.3.2 impact insulation class ≥ 55 IIC ASTM E492-09	ΔL _w = 21 dB Ln,w = 56 dB Pass 66 dB IIC Suitable for use on upper floors of residential high rise apartment buildings without the need for a separate acoustic underlay
 Indentation - residual	ISO 24343-1	Pass (≤ 0.1 mm)
 Impact resistance	EN 13329 Annex F	Pass (≥ 1800 mm)
 Castor chair continuous use	ISO 4918	Pass (25,000 cycles)
 Thermal resistance	ISO 8302	0.0515 m ² K/W Suitable for underfloor heating. Max 27°C
 Slip resistance³	AS4586:2013	See separate table
 Adhesive		None required; please install according to our installation instructions.
 Environmental	Floorscore SCS-EC10.3:2014 v4.0 Environmental Product Declaration ISO 14001 / ISO 9001	Indoor air quality certified; Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification) Manufactured to quality and environment management systems standards
 Recycling		Suitable
 Phthalate free		Yes

¹ 5G® is a patented technology invented by Välinge Innovation AB. The 5G® word mark and logo are registered trademarks owned by Välinge Innovation AB and any use of such marks is under license.

² Subject to terms. Please see our website.

³ Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

Every Karndean range and format meets our certification policy standards - be sure to verify the current certification status

For more information:

Call: 1800 33 11 70
Email: customerservice@karndean.com.au
Visit: www.karndeancommercial.com or www.karndean.com

May 25

	Product Code	Size		Box Quantity		Slip Resistance
		mm	inches	m ²	Pieces	
Wood Designs	SCB-VGW81T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW82T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW84T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW85T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW86T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW89T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW103T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW107T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW110T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW111T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW112T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW127T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW128T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW129T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW130T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW131T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW132T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW133T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW134T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3
	SCB-VGW135T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10, P3